




# SEALING TAPE (Meguro)

**GELSON®**AZIENDA CON SISTEMA QUALITÀ  
CERTIFICATO DA DNV  
UNI EN ISO 9001

## DATA SHEET

Rev. 1 dated 27/10/2008

For exchange Panels (doors, hoods, trunks). For cars, trucks, boats, vans and so on.  
It is quick and gives excellent finish, sealing of the door looks brand new.  
Working temperature recommended: 10/20°C.



### APPLICATION:

Completely eliminate previous sealing, silicone, oil, dust etc.  
Apply the sealing tape spray primer in two strokes. Allow 5 minutes to dry. (Be sure to use this primer for better adhesion and prevent corrosion).  
Apply the tape to desired places slowly.  
Use the roller to pressurize tape ("A" or "B" as you need).  
To fit the corners properly, cut the tape at a 45 angle. Take care of corners with conventional sealer as usual.  
Meguro tape is meant to be painted right away. If waterbased paints are used a previous application of primer on the tape is needed.



### STORAGE:

12 months in a cool, dry area in its original package (from +5°C to +25°C)

### PACKAGE SIZES AVAILABLE:

Code		Package size
56250	8 mm (W) * 16 m (L)	5 pcs
56260	10 mm (W) * 16 m (L)	5 pcs
56270	20 mm (W) * 8 m (L)	5 pcs
	<b>Spray Primer</b>	
56290		400 cc
	<b>Roller</b>	
56295		

*The effectiveness of our products is based on practical experience and research carried out in our laboratory. However, we decline any responsibility for work carried out, as it is evident that the result can be strongly influenced by a series of factors beyond our control.*