

FAST PRIMER

DESCRIPTION

1K anti-corrosion primer for metals.

It has very fast drying and excellent adhesion on a range of substrates such as steel, aluminum, and galvanized sheet metal, previously degreased and pickled. Indicated when you want to choose a rapid painting cycle without forgoing anticorrosive protection.

CHARACTERISTICS

Base: resins in solvent

Specific gravity: 1,0 g/cm³

Color: black, grey RAL 7035

Coverage: 8/10 m²/L ready to use

SUBSTRATE PREPARATION:

Can be applied on:

- Steel: degrease the substrate and remove any calamine.
- Galvanized sheet metal: degrease and phosphate the substrate.

Direct application on sheet metal is possible if limited to small uncovered areas.

APPLICATION:

Thin with 50% nitrocellulose thinner.

Application viscosity: 20 sec. Ford Cup n° 4 a 20 °C

Apply 1 coat with spray gun (recommended thickness 15-20 microns).

Clean tools with nitrocellulose thinner.

DRYING TIMES:

Dust dry: 10 minutes at 20°C

Thoroughly dry: 1 hour at 20°C

OVERPAINTING:

Can be painted over after 2 hours.

Can be painted over with Fondo 1C, Fondo 4+1 e Fondo 5+1 and other acrylic and polyurethane – based filler, or directly with nitrocellulose, synthetic or rapid drying enamels.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.