

CLEANER ACTIVATOR

DESCRIPTION

Silane-based cleaner/activator for sealants, suitable in general for all Gelflex and MS-Flex series, and in particular for glass sealants.

To be used on non-porous surfaces: glass, metal and various synthetic materials.

CHARACTERISTICS

- Appearance: clear liquid
- Base: silane solution
- Specific gravity: $0,81 \pm 0,02 \text{ g/cm}^3$

INSTRUCTIONS FOR USE

The surfaces to be treated must be perfectly clean, dry and degreased.

It can be applied by brush in thin layers or used as a cleaner/adhesion promoter by applying it with a soaked cloth.

The sealant should not be applied before 10 minutes (solvent evaporation). Drying times must be strictly observed.

Apply the sealant or adhesive not beyond 2 hours after coating with Cleaner Activator.

CAUTION: This product may permanently stain the surface. Clean residues immediately and do not let them dry. The product is sensitive to humidity: close the container immediately after use.

ACTIVATION WINDOW

At 20°C: min. 10 minutes – max. 2 hour

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.