

PASTA OPACIZZANTE PASTA OPACIZZANTE FINE

DESCRIPTION

Liquid buffing compounds.

These products are used in the case of touch-ups and partial coating of panels, when the old coat must be made even with the new one without making an abrupt cut.

In case of double-layer coatings, or other pastel-colored enamels, these compounds ensure a better adhesion between the old and the new coating.

These products avoid the danger of deep signs, which usually become evident only when the work is completed and the product has dried, thus compromising the final appearance. Moreover, there is no danger of "peeling" already painted corners.

Both products are water-based and leave surfaces clean, residue-free and ready for painting.

Free from silicone oils.

CHARACTERISTICS

Base: aqueous dispersion of synthetic abrasives

Appearance: creamy paste

Pasta opacizzante fine:

Colour: green

Specific gravity: 1,33 g/cm³ ± 0,05

Pasta opacizzante:

Colour: beige

Specific gravity: 1,44 g/cm³ ± 0,05

APPLICATION

Hand application.

Use a Kofle-X type abrasive pad, moistened and well wrung out, as a support. Apply a small amount of compound.

Start rubbing the surface to be buffed, exerting moderate pressure, until obtaining a matt and homogeneous surface.

Dry, remove any old residue, and the part is ready for painting.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.