

PUTTY REPAIR

Filler putty specifically formulated for repairing and rebuilding deep cuts, scratches and holes on natural leather, synthetic leather, hide or other materials in vehicle interiors. Maintains excellent plasticity even after drying.

CHARACTERISTICS

- Physical state: paste
- Base: mixture of polymers and fillers in aqueous emulsion
- Color: white
- PH: 8-10

SUBSTRATE PREPARATION

The surfaces to be treated must be perfectly clean and dry.
Confine the area to be treated with specific masking products.

APPLICATION

Apply, if necessary also in 3-4 passages waiting 2 hours between one coat and the next,, directly in the hole to be repaired, covering it completely using the sponge provided. be generous with the filler as the watery part evaporates during the drying phase, settling the product. Leave to dry for at least 16 hours.

SANDING

Sand with MAXFILM SUPER TACK sequence P180-P240-P320.

OVERCOATING

After at least 16 hours, overcoat with Putty Restore cod. 45PR or Color Restore cod. 45CR

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.