

FILLER CARBONIO NEW

DEFINITION

One-component, non-filming pore filler with high pigmentation; formulated for versatile applications in the Automotive and Marine sectors.

It can be applied directly on composite material/carbon fiber surfaces. Excellent filling and ease of application.

CHARACTERISTICS

- Chemical nature: solvent-based product
- Color: black
- Density: $1.56 \text{ g/cm}^3 \pm 0.03$
- Non-volatile content: $76\% \pm 2$

SUBSTRATE PREPARATION

Surfaces must be perfectly clean and dry. Applicable on carbon fiber and other composite materials.

Before application, it is recommended to carry out preliminary tests to check the compatibility of the product with the surface to be treated, considering the wide variety of application conditions and materials available on the market.

APPLICATION

Apply with a Hitex 4000 cloth, allow to air dry for 15-20 min at 20°C.

Remove any excess with ultra-fine abrasive pad/scouring pad.

Clean the surface with water-based anti-silicone cleaner and proceed with the painting cycle.

Do not blow with air.

Do not apply below 5°C. The final mechanical characteristics vary depending on the temperature at which the product was applied.

SANDING

Sanding is not necessary.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

OVERPAINTING

It can be overcoated with two-component acrylic fillers.

Due to the variety of coating cycles and application conditions, it is highly recommended to perform preliminary tests to verify the compatibility of the chosen coating system with the applied product. Each cycle must be evaluated in advance, as variables can significantly influence the final result.

STORAGE

Store the product in a dry environment, away from direct sunlight, and at temperatures in between 5°C and 30°C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.