

UNDERBODY PROTECTIVE COATING

DEFINITION

Bitumen-based protective and soundproofing coating agent, particularly suitable for underbodies of cars, trucks, buses, and industrial vehicles. It has a broad spectrum of adhesion to metallic surfaces.

Its strong points are:

- excellent resistance to alkaline and saline aqueous solutions
- excellent resistance to thermal excursions
- long-lasting anti-corrosion effect
- excellent verticality

Not overcoatable.

CHARACTERISTICS

- Chemical nature: Bituminous base
- Colours: black
- Density: $1.29 \text{ g/cm}^3 \pm 0.03$
- Non-volatile content: $65 \pm 2\%$

SUBSTRATE PREPARATION

Surfaces must be perfectly degreased, clean, and dry.

Before application, it is recommended to carry out preliminary tests to check the compatibility of the product with the surface to be treated, considering the wide variety of application conditions and materials available on the market.

APPLICATION

Ready-to-use product, does not require dilution.

Shake the product before use.

Apply with an Underbody gun (code 85102) at a pressure of 4/5 atm.

DRYING TIMES

- Dust-free (at 20°C): 20 minutes
- Full drying (at 20°C): 60 minutes

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

STORAGE

Store the product in a dry environment, away from direct sunlight, and at temperatures in between 5°C and 30°C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

GELSON S.r.l.

Lainate (Milan) 20045 Italy - Via Varese 11/13
TEL +39 029370640
FAX +39 0293570880
MAIL info@gelson.it

