

WB18 UNDERBODY

DEFINITION

A single-component protective and sound-deadening coating based on resins in an aqueous emulsion. Formulated for use as an underbody coating and stone chip protector on car, truck, and industrial vehicle bodywork.

It can be overcoated and has a VOC value of zero.

CHARACTERISTICS

- Chemical nature: resins in an aqueous emulsion
- Colours: white, black, grey
- Density: 1.33 g/cm³ ± 0.03
- Non- volatile content: 66 ± 2%
- Yield: 1.5-2 m²/l

SUBSTRATE PREPARATION

Surfaces must be perfectly degreased, clean, and dry. For application on bare metal, the use of an epoxy primer (such as Z41/42) is recommended.

Before application, it is recommended to carry out preliminary tests to check the compatibility of the product with the surface to be treated, considering the wide variety of application conditions and materials available on the market.

APPLICATION

Ready-to-use product, does not require dilution.

Shake the product before use.

Apply with a disposable cap gun 85440 and 85441. Spraying pressure: 4-5 atm.

Allow to flash off for 5-10 minutes between coats (at 20°C).

DRYING TIMES

- Dust-free (at 20°C): 90-120 minutes
- Full drying: 24 hours

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

OVERPAINTING

Can be overcoated with both water-based and solvent-based topcoats after flash-off (90-120 minutes).

Due to the variety of coating cycles and application conditions, it is highly recommended to perform preliminary tests to verify the compatibility of the chosen coating system with the applied product. Each cycle must be evaluated in advance, as variables can significantly influence the final result.

STORAGE

Store the product in a dry environment, away from direct sunlight, and at temperatures in between 5°C and 30°C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

GELSON S.r.l.

Lainate (Milan) 20045 Italy - Via Varese 11/13
TEL +39 029370640
FAX +39 0293570880
MAIL info@gelson.it

