

SPRAY FILLER UP

DEFINITION

One-component acrylic primer spray, high filling properties.

Developed for car body repair, its filling power makes it suitable for small repairs (Spot Repair) such as filling sanding marks or irregular surfaces before the application of the basecoat, during the painting cycle.

It is formulated with anti-corrosion pigments and is overcoatable with most systems available on the market.

CHARACTERISTICS

- Chemical nature: acrylic resin
- Color: grey, white
- Coverage: 11.5 m²/can

SUBSTRATE PREPARATION

Surfaces must be perfectly degreased, clean, and dry. Applicable on:

- steel;
- aluminum;
- galvanized sheet metal, carefully degreased and pickled;
- fiberglass;
- painted bumpers;

Before application, preliminary tests are recommended to verify the product's compatibility with the surface to be treated, considering the wide variety of application conditions and materials available on the market.

APPLICATION

Shake the container for at least 2 minutes.

Apply at a distance of 15-20 cm from the surface; apply 1-3 coats with a flash-off time of 5 minutes between coats.

Do not apply at temperatures below 5° C.

SANDING

In case of overcoating with solvent-based systems, sanding is not required. For water-based systems or in case of dirt, lightly dry sand with P400-600 paper (Super Assilex Sky).

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

OVERCOATING

Overcoatable with most systems on the market 20-30 minutes after application (at 20°C).

Given the variety of painting cycles and application conditions, it is recommended to perform preliminary tests to verify the compatibility of the chosen coating system with the applied product. Each cycle must be evaluated in advance, as variables can significantly influence the final result.

STORAGE

Store in a cool, dry place, protected from direct sunlight at temperatures between 5° C and 30° C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.