

ADHESIVE DOORS SKIN

DEFINITION

Adhesive polyethylene film used for temporary protection, strictly for indoor use only.

It protects the surface from dirt, scratches, and tool marks.

It **does not** protect against corrosion, moisture, or chemicals.

GENERAL CHARACTERISTICS

- Chemical nature: low-density polyethylene (LDPE)
- Adhesive type: modified acrylic
- Available dimensions: 650mm x 50m, 600mm x 10m
- Average film thickness: 100 microns
- Breaking load*: Longitudinal: 17 ± 3 N/cm – Transversal: 11 ± 3 N/cm
- Max elongation*: Longitudinal: >450% – Transversal: >850%

*AFERA and DIN standards

INSTRUCTIONS FOR USE

Apply to surfaces that are free of grease, oil, solvents, and dust. Apply the film without excessive tension and ensure no wrinkles or bubbles are left.

Application temperature: from +10°C to +40°C.

STORAGE

Store for 12 months in a cool, dry place.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

GELSON S.r.l.

Lainate (Milan) 20045 Italy - Via Varese 11/13
TEL +39 029370640
FAX +39 0293570880
MAIL info@gelson.it

