

## SPACIAL DOUBLE SIDED TAPE STRONG ADHERENCE

### DEFINITION

High-performance acrylic foam double-sided tape.

Suitable for permanent structural bonding, it develops exceptional adhesive strength within approximately 72 hours of application.

Its excellent resistance to UV rays, water, extreme temperatures, and solvents makes it suitable for both outdoor and indoor applications.

It is suitable for bonding a wide range of materials, including high surface energy substrates such as steel, aluminum, and ABS.

### CHARACTERISTICS

- Total Thickness: 1.2 mm
- Colour: grey
- Adhesive: acrylate
- Liner: plastic film
- Density/Specific Weight: 800 kg/m<sup>3</sup>
- Adhesion Strength (AFERA 5001): 78 N/25 mm
- Temperature Resistance (Long Term): from -30°C to +120°C
- Temperature Resistance (Short Term): +180°C

### STORAGE

Store in a cool, dry place, protected from direct sunlight (recommended conditions: 20°C; 55% r.h.).

*The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.*

\* For any information about product codes or packs, please see our catalogue, our price list or contact us.