

FAST FINISH

DEFINITION

Glossy spray clearcoat based on acrylic resins.

One-component formulation characterized by high gloss and good weathering resistance.

Its application is recommended for touch-up and coating of small surface areas.

CHARACTERISTICS

- Chemical nature: acrylic resin
- Gloss (60°, 15–20 µm): approx. 90 Gloss Units

SUBSTRATE PREPARATION

Suitable for application over matte water-based and solvent-based bases, both polyester and acrylic.

It is recommended to perform a preliminary test on a hidden area in order to verify compatibility with the substrate.

APPLICATION

Shake the can so that the mixing ball rotates vigorously for at least 20 seconds.

It is also recommended to shake the can occasionally during use.

Spray evenly from a distance of approximately 20–30 cm, applying a first light coat.

After a few moments, apply a second horizontal coat immediately followed by a third vertical coat.

After use, spray the product for 2–3 seconds with the can inverted to prevent nozzle clogging.

DRYING TIMES

- Dust-free (20°C): 12 minutes
- Touch dry (20°C): 30 minutes
- Through dry (20°C): 24 hours

STORAGE

Store in a cool, dry environment, protected from direct sunlight, and at temperatures between 5°C and 35°C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.