

KIT NANOTEC - POPUP

Nanometric renewable treatment. The trigger sprayer makes application quick and easy.

The nanoceramic polymer modifies the surface characteristics, making it water-repellent, improving its resistance to light abrasions, dirt, and atmospheric agents, guaranteeing a deep and durable shine, reducing the effort for maintenance and cleaning.

This treatment alone gives short-lasting results (6 months).

Can be used for semestral maintenance of vehicles that have been treated with one of the NANOTEC kits (codes 45NTLL and 45NTR).

KIT CONTENT

- POP-UP - 100 mL
- 1 microfiber gold cloth
- 1 microfiber orange cloth

APPLICATION CONDITIONS

Ideal application temperature: from 10°C to 25°C. Do not apply above 30°C.

Do not apply in direct sunlight. Do not apply on hot surfaces.

Do not apply on matt coatings.

SUBSTRATE PREPARATION

WASH OUT and SET UP products are contained in the CAR CARE KIT - PREPARING (code 45CCP).

00. WARNING

- Before starting, make sure that the surface to be treated is perfectly polished and free from defects. Wash the vehicle and decontaminate chemically and mechanically. Every imperfection, if not completely removed, will compromise the final appearance. If any defect is found, polish the vehicle before proceeding.
- For newly painted vehicles, make sure that the coating has fully cured (check the supplier's technical documentation)
- The cloths must always be perfectly clean throughout the preparation and application process. It is recommended to use a cloth for each product to avoid contamination between them. When wiping the surface dry, change the side of the cloth frequently. Once a cloth has been used in all its parts, get a new one.

01. Application of WASH OUT

- Spray the product directly on the surface, then spread it with a green microfiber cloth to detach waxes and dirt.
- Wait for a few minutes. You will see the product dry, and the surface become slightly dull.
- Rinse with pressure washer and remove excess with a wet red microfibre cloth.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

- Rinse and dry with a grey and red double-face microfibre cloth.
- Blow with compressed air.

02. Application of SET UP

- Spray the product directly on the surface, then spread it with a red microfibre cloth.
- Wipe the surface dry with a clean gold microfibre cloth.

NANOCOATING APPLICATION

03. Application of POP UP

- Spray the product directly on the surface and on the ORANGE microfibre cloth. Spread the product evenly. Proceed by dividing the surface into small areas of about 50 x 50 cm at a time. Wait 20-30 seconds to 1 minute, until the product layer is divided in small drops. Polish using a GOLD microfibre cloth.

Keep the vehicle indoor and avoid wetting and touching the treated surface for at least 48h to allow the product to fully cure. Wait at least 7 days before washing.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

GELSON S.r.l.

Lainate (Milan) 20045 Italy - Via Varese 11/13
 TEL +39 029370640
 FAX +39 0293570880
 MAIL info@gelson.it

