

KIT DEFENDER 2K

DEFINITION

High-performance, high-gloss nanometric two-pack system. Once cured, this product forms an invisible, flexible and hard layer that gives protection and gloss to painted car body surfaces.

It enhances resistance to scratches, weathering, and other agents such as tree sap and bird droppings.

Long-lasting performance.

KIT CONTENT

45780 - DEFENDER CLEANER 200ml
 45760 - DEFENDER (PART A) 75ml
 45770 - CATALYST 37,5 ml
 86340/115N - MANUAL POLISHING PAD 1PC
 48340/1 - GOLD MICROFIBER CLOTH 1PC
 48370/1 - ORANGE MICROFIBER CLOTH 1PC

CHARACTERISTICS

DEFENDER (Part A)

- Specific gravity: $0,88 \pm 0,03 \text{ g/cm}^3$
- Colour: blue

CATALYST (Part B):

- Specific gravity: $0,99 \pm 0,03 \text{ g/cm}^3$
- Colour: clear, yellowish

APPLICATION

- 1) Surfaces to be painted must be clean and free of defects. Otherwise, polish the surface.
- 2) Clean the surface with Defender Cleaner to remove any dirt or residues. Always use the orange microfiber cloth (code 48370) for this operation.
- 3) Mix part A very well before use, then blend part A and B in the ratio of 2 to 1 in volume and mix thoroughly.
- 4) Using the included applicator pad, apply the Defender mixture spreading it evenly in a single direction. DO NOT apply Defender with semi-circular movements!
- 5) Dry in oven for 30 min at 60°C. Oven-drying enhances the product performances, giving a more resistant and longer lasting result. Alternatively, let dry for 40 to 50 min at 20°C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

- 6) Once the substrate has cooled down, then remove any residue using the orange microfiber cloth (code48370) to obtain an even surface.

WARNING

- The surfaces to be treated must be completely dry.
- Do not apply in direct sunlight or at high temperatures (>25°C).
- Stir the mixture thoroughly before each application.
- The mixture will last for 2-3 hours depending on temperature and humidity.
- To allow for full reticulation, wait at least 48 hours before washing the car.
- Any cloths, pads, gloves or containers used for Defender must be kept separately to prevent contamination.
- When repainting, treat the surface with Assilex Lemon or Orange.

After removing excess material with a cloth, do not wash or rinse the used cloth under running water. Dispose in accordance with applicable regulations.

STORAGE

Store in a cool, dry environment, protected from direct sunlight, and at temperatures between 5°C and 30°C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

GELSON S.r.l.

Lainate (Milan) 20045 Italy - Via Varese 11/13
 TEL +39 029370640
 FAX +39 0293570880
 MAIL info@gelson.it

