GELSON
la qualità è passione

TECHNICAL DATA SHEET

REV.1 08/07/2026

DW180 – DEWAXER FOR SOLVENT BASE WAX

DEFINITION

Special remover for paraffinic waxes. Can be applied with a pressure washer. Removes protective waxes (codes 20500-20501: solvent-based protective wax / cera protettiva a solvente, Lt 5-Lt 18).

CHARACTERISTICS

- Chemical nature: solvent-based product
- Appearance: clear liquid
- Density: 0,83 g/cm^3 ± 0,02

APPLICATION

Apply the product using a pressure washer at a temperature of 90-100°C.
Spray the product evenly on the car, at approx. 15-20 cm. Rinse thoroughly with warm water.
Application by hand is also possible: spray the cold undiluted product, then wipe with a glove or a sponge. Rinse thoroughly with warm water.
Once the wax has been removed, wash the car with shampoo or cleaner.

STORAGE

Store the product in a dry place, protected from direct sunlight, at temperatures between 5°C and 35°C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

GELSON S.r.l.

Lainate (Milan) 20045 Italy - Via Varese 11/13
TEL +39 029370640
FAX +39 0293570880
MAIL info@gelson.it

QUALITY SYSTEM CERTIFICATION DNV ISO 9001