

CAR PROTECTOR

DEFINITION

Temporary coating for metals and coated surfaces. The clear protective layer does not affect substrate appearance and gloss.

It has been especially formulated for the protection of vehicles stocked outdoor: it resists the effects of rain, UV-rays and bird droppings. The formulation does not contain any solvent that could attack coating or plastic and rubber parts.

Can be easily removed with remover DWX190 for water-based waxes or with alkaline water solution.

CHARACTERISTICS

- Chemical nature: acrylic polymer in hydro-alcoholic solution.
- Color: clear - yellowish
- Density: $0.93 \text{ g/cm}^3 \pm 0.03$
- Non-volatile matter: $15 \pm 2\%$
- pH: 7.4 ± 0.4

APPLICATION

The product is ready to use and should not be thinned. Apply with spray gun.

Recommended film thickness: wet film: 40 - 60 μm , dry film: 6 - 10 μm

The product can be easily removed with DWX190 (code 20190), added to water in ratio 1:3 to 1:4, or with an alkaline water-based dewaxing solution.

Spray with mixed-air or airless systems, both handheld and automatized.

DRYING TIMES

Dust-dry (20°C): 10-20 minutes

STORAGE

Store the product in a dry place, protected from direct sunlight, at temperatures between 5°C and 35°C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.