

GEL CABIN

DEFINITION

Gel-Cabin is a water based transparent liquid with sticky properties, which is applied in a thin layer in spray cabins., where it collects and retains dust particles.

It can be applied onto walls, ceilings, lights and ventiducts in spray cabins.

Once the watery part has dried, the resulting clear and transparent surface will keep its sticky properties for a long time, capturing paint overspray, dust and other small particles during the painting.

CHARACTERISTICS

- Chemical nature: aqueous solution
- Density: $1.04 \text{ g/cm}^3 \pm 0.03$
- pH: 6,4 - 7,0
- Colour: transparent clear / light yellow
- Usage: 10/15 m²/1liter
- Non-volatile matter: $25 \pm 2\%$

APPLICATION

The surface to be treated must be clean, dry and degreased.

Gel Cabin is ready to use and can be applied by brush, by roll or with a spray gun (P=2 - 3 atm.)

It should be removed and reapplied every 2/3 months, or more often if saturated by a frequent use of the spray cabin.

It can be easily removed by hot water or using a steam jet cleaner.

STORAGE

Store the product in a dry place, protected from direct sunlight, at temperatures between 5°C and 35°C. Gel Cabin is bio-degradable. Keep away from frost.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.