

844 BRUSH SEALANT

DEFINITION

One-component sealer, can be applied by brush for sealing automotive body components, particularly interior areas such as engine compartments and luggage compartments.

The product offers excellent adhesion and easy application, with a non-stringing consistency for improved workability. Can be overpainted.

CHARACTERISTICS

- Chemical base: Synthetic rubber in solvent
- Colour: grey
- Density: $1.35 \text{ g/cm}^3 \pm 0.02$
- Non-volatile matter: $69 \pm 1\%$

APPLICATION

Can be applied by brush directly on:

- Properly degreased and sanded bare metal;
- Existing paintwork, previously sanded with P80 abrasive;
- Fibreglass (GRP) and composite materials.

DRYING TIMES

- Dust-free: 2 hours
- Fully cured: 1 to 3 days, depending on the applied film thickness.

OVERPAINTING

Can be overpainted after complete drying with any type of automotive topcoat.

Due to the wide variety of paint systems and application conditions, preliminary testing is recommended to verify the compatibility of the selected coating system with the applied product. Each paint system should be evaluated in advance, as application variables may significantly affect the final result.

STORAGE

Store the product in a dry place, protected from direct sunlight, at temperatures between 5°C and 35°C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.