

GELFLEX 345 SPEED - CLEANER ACTIVATOR

DEFINITION

Solvent-based cleaner/activator for sealants, specifically formulated for Gelflex 345 Speed windscreen sealant, allowing it to adhere to the support without the use of Black Glass Primer.

CHARACTERISTICS

- Chemical nature: silane solution
- Appearance: clear liquid
- Density : 0,73 ± 0,02 g/cm³

INSTRUCTIONS FOR USE

The surfaces to be treated must be perfectly clean, dry and degreased.

Cleaning the support is essential for obtaining a strong joint. If the surface is heavily contaminated, clean it with a solvent-based product such as Defender Cleaner and, if necessary, an abrasive sponge such as Koflex. Apply to both the surfaces to be joined. Use a swab or lint-free cloth. Apply the product evenly in one direction, avoiding cross-coating.

The sealant should not be applied before 10 minutes (solvent evaporation). Drying times must be strictly observed.

Apply the sealant not beyond 1 hour after coating with Cleaner.

CAUTION: the product is very reactive and therefore sensitive to humidity and contamination. Do not dip the same applicator in the product again after use.

Close the container immediately after use.

Pay attention to any change in appearance (turbidity, coloration) and do not use the product if they occur.

Once opened, the product must be used within one month.

ACTIVATION WINDOW

At 20°C: min. 10 minutes - max. 1 hour

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

STORAGE

Store the product in a dry place, protected from direct sunlight, at temperatures between 10°C and 35°C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

GELSON S.r.l.

Lainate (Milan) 20045 Italy - Via Varese 11/13
TEL +39 029370640
FAX +39 0293570880
MAIL info@gelson.it

