GELSON
la qualità è passione

TECHNICAL DATA SHEET

REV.4 29/07/2026

CLEANER ACTIVATOR

DEFINITION

Silane-based cleaner/activator for sealants, suitable in general for all Gelflex and MS-Flex series, especially for glass sealants.
To be used on non-porous surfaces: glass, metal and various synthetic materials.

CHARACTERISTICS

- Chemical nature: silane solution
- Appearance: clear liquid
- Density : 0,81 ± 0,02 g/cm^3

INSTRUCTIONS FOR USE

The surfaces to be treated must be perfectly clean, dry and degreased.
It can be applied by brush in thin layers or used as a cleaner/adhesion promoter by applying it with a soaked cloth. Apply the product evenly in one direction, avoiding cross-coating.
The sealant should not be applied before 10 minutes (solvent evaporation). Drying times must be strictly observed.
Apply the sealant or adhesive not beyond 2 hours after coating with Cleaner Activator.

CAUTION: This product may permanently stain the surface. Clean residues immediately and do not let them dry. The product is sensitive to humidity: close the container immediately after use.

ACTIVATION WINDOW

At 20°C: min. 10 minutes - max. 2 hour

STORAGE

Store the product in a dry place, protected from direct sunlight, at temperatures between 10°C and 35°C.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.

GELSON S.r.l.

Lainate (Milan) 20045 Italy - Via Varese 11/13
TEL +39 029370640
FAX +39 0293570880
MAIL info@gelson.it

QUALITY SYSTEM CERTIFICATION DNV ISO 9001